

**Environmental
Product
Declaration**

According to ISO14025+EN15804 A2 (+indicators A1)

This declaration is for:

Firesafe FSP

Provided by:

Firesafe AS



MRPI® registration:

1.1.00896.2025

Program operator:

Stichting MRPI®

Publisher:

Stichting MRPI®

www.mrpi.nl

Date of first issue:

9-7-2025

Date of this issue:

9-7-2025

Expiry date:

9-7-2030

COMPANY INFORMATION

Firesafe AS
 Robsrudskogen 15
 1470
 Lørenskog
 Norway
 +47 22 72 20 20
 Pål Paulsen
 firesafe.no

MRPI® REGISTRATION

1.1.00896.2025

DATE OF THIS ISSUE

9-7-2025

EXPIRY DATE

9-7-2030

SCOPE OF DECLARATION

This MRPI®-EPD certificate is verified by Anne Kees Jeeninga, Advieslab VOF. The LCA study has been done by Martijn Blaak, EcoReview. The certificate is based on an LCA-dossier according to ISO14025+EN15804 A2 (+indicators A1). It is verified according to the 'MRPI®-EPD verification protocol November 2020.v4.0'. EPDs of construction products may not be comparable if they do not comply with EN15804+A2. Declaration of SVHC that are listed on the 'Candidate list of Substances of Very High Concern for authorisation' when content exceeds the limits for registration with ECHA.

PROGRAM OPERATOR

Stichting MRPI®
 Kingsfordweg 151
 1043 GR
 Amsterdam

PRODUCT

Firesafe FSP

DECLARED UNIT / FUNCTIONAL UNIT

1 Mass (kg)

DESCRIPTION OF PRODUCT



water-based fire-resistant paint

VISUAL PRODUCT



MORE INFORMATION

firesafe.no

Ing. L. L. Oosterveen MSc. MBA Managing Director MRPI 	DEMONSTRATION OF VERIFICATION
	CEN standard EN15804 serves as the core PCR [1]
	Independent verification of the declaration and data according to ISO14025+EN15804 A2 (+indicators A1) Internal: External: X
	Third party verifier: Anne Kees Jeeninga, Advieslab VOF  [1] PCR = Product Category Rules

DETAILED PRODUCT DESCRIPTION (PART 1)

Firesafe FSP is a waterborne firestop coating based on a sustainable polymer system manufactured by Firesafe AS. Among other things, this coating is used for the fire-resistant treatment of rock wool Firesafe FSB1 & Firesafe FSB2 fire stopping boards and around cable trays and pipe and cable penetrations. This provides a fire-resistant and smoke-proof seal to adjacent rooms. Firesafe FSP is produced per kilo, the reference service life of Firesafe FSP is 25 years.

Component (> 1%)	(%)
Emulsion	29,80%
Water	24,30%
Filler	27,70%
Flame retardant	12,60%
Flame retardant	10,07%

SCOPE AND TYPE

This Environmental Product Declaration (EPD) has been prepared for Firesafe FSP manufactured and sold by FireSafe AS. The scope of the EPD is from cradle to gate, following the requirements of EN 15804+A2 and ISO 14025. The following specifications apply:

The manufacturing of the Firesafe FSP takes place at Multimolecules in Kaatsheuvel, Netherlands.

The product is primarily applied within Norway. 1250 km is used as a distance for transport to the Firesafe warehouse in in Lørenskog, + 300 km fixed distance for distribution in accordance with Norwegian standards.

The end-of-life treatment of the product is assumed to take place in Norway based on current market practice.

All background data is sourced from Ecoinvent version 3.6.

The study was conducted using SimaPro version 9.5.1.

This EPD is a product-specific EPD, representing the environmental performance of a specific product from Firesafe, based on primary data collected in 2024 and verified secondary sources.


This declaration is specific to Firesafe FSP.

This product is in compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR).

PRODUCT STAGE			CONSTRUCTION PROCESS STAGE		USE STAGE							END OF LIFE STAGE				BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARIES
Raw material supply	Transport	Manufacturing	Transport gate to site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse - Recovery - Recycling potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x

X = Modules Assessed

ND = Not Declared



ENVIRONMENTAL IMPACT per functional unit or declared unit (indicators A1)

	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
ADPE	kg Sb eq.	2,38E-05	2,89E-06	3,82E-06	3,05E-05	4,87E-07	4,53E-06	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	1,29E-07	0,00E+00	1,49E-07	0,00E+00
ADPF	MJ	3,60E+01	2,61E+00	5,56E+00	4,42E+01	4,40E-01	5,56E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	7,75E-02	0,00E+00	3,56E-01	0,00E+00
GWP	kg CO2 eq.	1,68E+00	1,68E-01	3,32E-01	2,18E+00	2,83E-02	4,53E-01	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	5,07E-03	0,00E+00	6,30E-01	0,00E+00
ODP	kg CFC11 eq.	9,62E-08	3,18E-08	2,33E-08	1,51E-07	5,37E-09	1,82E-08	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	8,99E-10	0,00E+00	2,96E-09	0,00E+00
POCP	kg ethene eq.	1,13E-03	1,02E-04	1,27E-04	1,36E-03	1,73E-05	2,12E-04	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	3,06E-06	0,00E+00	1,43E-04	0,00E+00
AP	kg SO2 eq.	9,44E-03	4,39E-04	1,02E-03	1,09E-02	7,37E-05	1,57E-03	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	2,23E-05	0,00E+00	1,43E-04	0,00E+00
EP	kg (PO4) 3 eq.	8,27E-04	7,25E-05	1,45E-04	1,04E-03	1,21E-05	2,36E-04	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	4,38E-06	0,00E+00	5,96E-04	0,00E+00

Toxicity indicators and ECI (Dutch market)

HTP	kg DCB eq.	7,36E-01	3,61E-02	1,27E-01	9,00E-01	6,09E-03	1,34E-01	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	2,13E-03	0,00E+00	2,63E-02	0,00E+00
FAETP	kg DCB eq.	6,67E-02	1,52E-03	5,66E-03	7,39E-02	2,56E-04	1,20E-02	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	6,23E-05	0,00E+00	2,41E-03	0,00E+00
MAETP	kg DCB eq.	8,19E+01	4,11E+00	9,96E+00	9,60E+01	6,94E-01	1,63E+01	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	2,24E-01	0,00E+00	5,99E+00	0,00E+00
TETP	kg DCB eq.	2,14E-03	2,04E-04	2,88E-03	5,22E-03	3,44E-05	7,79E-04	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	7,54E-06	0,00E+00	8,33E-05	0,00E+00
ECI	euro	2,11E-01	1,49E-02	3,55E-02	2,61E-01	2,52E-03	4,60E-02	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	6,11E-04	0,00E+00	4,08E-02	0,00E+00
ADPF	kg Sb eq.	1,73E-02	1,25E-03	2,67E-03	2,13E-02	2,11E-04	2,67E-03	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	3,73E-05	0,00E+00	1,71E-04	0,00E+00

- ADPE = Abiotic Depletion Potential for non-fossil resources
- ADPF = Abiotic Depletion Potential for fossil resources
- GWP = Global Warming Potential
- ODP = Depletion potential of the stratospheric ozone layer
- POCP = Formation potential of tropospheric ozone photochemical oxidants
- AP = Acidification Potential of land and water
- EP = Eutrophication Potential
- HTP = Human Toxicity Potential
- FAETP = Fresh water aquatic ecotoxicity potential
- MAETP = Marine aquatic ecotoxicity potential
- TETP = Terrestrial ecotoxicity potential
- ECI = Environmental Cost Indicator
- ADPF = Abiotic Depletion Potential for fossil resources

ENVIRONMENTAL IMPACT per functional unit or declared unit (core indicators A2)

Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP-total kg CO2 eq.	1,74E+00	1,69E-01	3,59E-01	2,27E+00	2,86E-02	5,10E-01	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	5,11E-03	0,00E+00	9,57E-01	0,00E+00
GWP-fossil kg CO2 eq.	1,74E+00	1,69E-01	3,03E-01	2,21E+00	2,86E-02	3,75E-01	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	5,11E-03	0,00E+00	6,01E-02	0,00E+00
GWP-biogenic kg CO2 eq.	2,64E-04	8,16E-05	5,59E-02	5,62E-02	1,38E-05	1,35E-01	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	2,36E-06	0,00E+00	8,97E-01	0,00E+00
GWP-luluc kg CO2 eq.	9,28E-04	4,22E-05	1,11E-04	1,08E-03	7,12E-06	1,57E-04	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	1,87E-06	0,00E+00	1,80E-05	0,00E+00
ODP kg CFC11 eq.	1,07E-07	4,00E-08	2,52E-08	1,72E-07	6,74E-09	2,09E-08	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	1,13E-09	0,00E+00	3,61E-09	0,00E+00
AP mol H+ eq.	1,10E-02	5,47E-04	1,22E-03	1,28E-02	9,18E-05	1,84E-03	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	2,96E-05	0,00E+00	1,80E-04	0,00E+00
EP-fresh water kg PO4 eq.	4,73E-05	1,18E-06	8,93E-06	5,74E-05	1,99E-07	8,95E-06	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	5,15E-08	0,00E+00	5,39E-06	0,00E+00
EP-marine kg N eq.	1,34E-03	1,26E-04	2,61E-04	1,73E-03	2,11E-05	4,27E-04	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	1,04E-05	0,00E+00	1,27E-03	0,00E+00
EP-terrestrial mol N eq.	1,44E-02	1,42E-03	2,05E-03	1,79E-02	2,37E-04	2,64E-03	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	1,15E-04	0,00E+00	4,89E-04	0,00E+00
POCP kg NMVOC eq.	5,27E-03	5,31E-04	6,83E-04	6,48E-03	8,89E-05	9,75E-04	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	3,29E-05	0,00E+00	3,51E-04	0,00E+00
ADP-minerals & metals kg Sb eq.	2,38E-05	2,89E-06	3,81E-06	3,05E-05	4,87E-07	4,53E-06	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	1,29E-07	0,00E+00	1,49E-07	0,00E+00
ADP-fossil MJ, net calorific value	3,48E+01	2,63E+00	5,19E+00	4,26E+01	4,44E-01	5,43E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	7,71E-02	0,00E+00	3,40E-01	0,00E+00
WDP m3 world eq. Deprived	9,53E-01	1,11E-02	9,15E-02	1,06E+00	1,89E-03	1,48E-01	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	2,76E-04	0,00E+00	1,18E-02	0,00E+00

GWP-total = Global Warming Potential total

GWP-fossil = Global Warming Potential fossil fuels

GWP-biogenic = Global Warming Potential biogenic

GWP-luluc = Global Warming Potential land use and land use change

ODP = Depletion potential of the stratospheric ozone layer

AP = Acidification Potential, Accumulated Exceedence

EP-freshwater = Eutrophication Potential, fraction of nutrients reaching freshwater end compartment

EP-marine = Eutrophication Potential, fraction of nutrients reaching marine end compartment

EP-terrestrial = Eutrophication Potential, Accumulated Exceedence

POCP = Formation potential of tropospheric ozone photochemical oxidants

ADP-minerals & metals = Abiotic Depletion Potential for non-fossil resources [1]

ADP-fossil = Abiotic Depletion for fossil resources potential [1]

WDP = Water (user) deprivation potential, deprivation-weighted water consumption [1]

Disclaimer [1]:

- The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.

ENVIRONMENTAL IMPACT per functional unit or declared unit (additional indicators A2)

Unit		A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
PM	Disease incidence	7,11E-08	1,18E-08	7,68E-09	9,05E-08	1,98E-09	1,37E-08	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	4,59E-10	0,00E+00	2,10E-09	0,00E+00
IRP	kBq U235 eq.	4,89E-02	1,13E-02	8,70E-03	6,89E-02	1,91E-03	1,04E-02	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	3,23E-04	0,00E+00	1,36E-03	0,00E+00
ETP-fw	CTUe	3,07E+01	1,92E+00	5,34E+00	3,79E+01	3,24E-01	6,19E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	6,87E-02	0,00E+00	5,13E+00	0,00E+00
HTP-c	CTUh	1,66E-09	4,86E-11	3,46E-10	2,05E-09	8,19E-12	3,00E-10	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	2,23E-12	0,00E+00	3,19E-11	0,00E+00
HTP-nc	CTUh	3,22E-08	1,55E-09	8,13E-09	4,19E-08	2,61E-10	6,36E-09	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	7,52E-11	0,00E+00	1,55E-09	0,00E+00
SQP	-	5,50E+00	3,01E+00	6,42E-01	9,15E+00	5,07E-01	1,53E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	6,68E-02	0,00E+00	6,10E-01	0,00E+00

- PM = Potential incidence of disease due to PM emissions
- IRP = Potential Human exposure efficiency relative to U235 [1]
- ETP-fw = Potential Comparative Toxic Unit for ecosystems [2]
- HTP-c = Potential Comparative Toxic Unit for humans, cancer [2]
- HTP-nc = Potential Comparative Toxic Unit for humans, non-cancer [2]
- SQP = Potential soil quality index [2]

Disclaimer [1]:

- This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste.

Disclaimer [2]:

- The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.

OUTPUT FLOWS AND WASTE CATEGORIES per functional unit or declared unit (A1 en A2)

	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
HWD	kg	1,68E-05	6,50E-06	7,68E-06	3,10E-05	1,10E-06	4,01E-06	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	1,95E-07	0,00E+00	1,13E-06	0,00E+00
NHWD	kg	3,67E-01	2,29E-01	9,81E-02	6,94E-01	3,86E-02	2,52E-01	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	4,89E-03	0,00E+00	1,00E+00	0,00E+00
RWD	kg	4,98E-05	1,79E-05	8,37E-06	7,60E-05	3,01E-06	1,16E-05	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	5,06E-07	0,00E+00	1,76E-06	0,00E+00
CRU	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
MFR	kg	0,00E+00	0,00E+00	1,82E-04	1,82E-04	0,00E+00	2,73E-05	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
MER	kg	0,00E+00	0,00E+00	9,79E-06	9,79E-06	0,00E+00	1,47E-06	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
EEE	MJ	0,00E+00	0,00E+00	6,63E-04	6,63E-04	0,00E+00	9,95E-05	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
ETE	MJ	0,00E+00	0,00E+00	1,14E-03	1,14E-03	0,00E+00	1,71E-04	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00

HWD = Hazardous Waste Disposed
 NHWD = Non Hazardous Waste Disposed
 RWD = Radioactive Waste Disposed
 CRU = Components for reuse
 MFR = Materials for recycling
 MER = Materials for energy recovery
 EEE = Exported Electrical Energy
 ETE = Exported Thermal Energy

RESOURCE USE per functional unit or declared unit (A1 and A2)

	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
PERE	MJ	0,00E+00	0,00E+00	8,23E-03	8,23E-03	0,00E+00	1,23E-03	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
PERM	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
PERT	MJ	1,36E+00	2,70E-02	1,45E-01	1,53E+00	4,55E-03	2,19E-01	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	9,65E-04	0,00E+00	1,47E-02	0,00E+00
PENRE	MJ	0,00E+00	0,00E+00	2,80E+00	2,80E+00	0,00E+00	4,20E-01	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
PENRM	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
PENRT	MJ	3,73E+01	2,79E+00	5,62E+00	4,57E+01	4,71E-01	5,79E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	8,18E-02	0,00E+00	3,62E-01	0,00E+00
SM	kg	0,00E+00	0,00E+00	5,55E-05	5,55E-05	0,00E+00	8,33E-06	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
RSF	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
NSRF	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
FW	m3	2,46E-02	3,35E-04	2,62E-03	2,75E-02	5,67E-05	3,92E-03	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	9,39E-06	0,00E+00	3,13E-04	0,00E+00

PERE	=	Use of renewable primary energy excluding renewable primary energy used as raw materials
PERM	=	Use of renewable primary energy resources used as raw materials
PERT	=	Total use of renewable primary energy resources
PENRE	=	Use of non-renewable primary energy resources excluding non-renewable energy resources used as raw materials
PENRM	=	Use of non-renewable primary energy resources used as raw materials
PENRT	=	Total use of non-renewable primary energy resources
SM	=	Use of secondary materials
RSF	=	Use of renewable secondary fuels
NSRF	=	Use of non-renewable secondary fuels
FW	=	Use of net fresh water

BIOGENIC CARBON CONTENT per functional unit or declared unit (A1 and A2)

	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
BBCpr	kg C	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
BCCpa	kg C	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00

BCCpr	=	Biogenic carbon content in product
BCCpa	=	Biogenic carbon content in packaging

CALCULATION RULES (PART 1)

This study follows the modular structure of EN 15804+A2 and ISO 14044. The declared unit is 1kg of Firesafe FSP. All lifecycle stages from raw material extraction through end-of-life are included. The functional unit is based on 1 kg of product ready for use. No significant input or output flows have been deliberately excluded.

Primary data was collected from Firesafe AS, covering production inputs, electricity use, welding operations, transport, and end-of-life scenarios. Background data was sourced from the Ecoinvent 3.6 database. Data quality is considered “good” to “very good” for all records in terms of time, geography, and technology representativeness, as assessed per EN 15804+A2 Annex E.

All primary data used in this study refers to the calendar year 2024. Background data (Ecoinvent v3.6) reflects datasets published and updated as of July 2024. No economic or mass allocations were necessary within the main product system. Recycling allocation for Module D follows the substitution approach, consistent with EN 15804+A2 guidance.

SCENARIOS AND ADDITIONAL TECHNICAL INFORMATION (PART 1)

Description of processes within A1–A3 (Production Stage)

A1 – Raw material supply:

Includes the extraction and processing of input materials.

A2 – Transport:

Transport of input materials to the manufacturing plant by truck. Distances are based on distance between supplier and manufacturing plant in Kaatsheuvel.

A3 – Manufacturing:

Includes electricity, gas usage and water usage. Material losses and waste treatment are included.

Electricity Mix – Global Warming Potential (GWP):

The NMD profile 0510-pro&Elektriciteitsverbruik, bouwmaschine elektrisch, Grijze mix, per kWh input (electricity: 3.6 MJ/kWh; 3.6 MJ input equals 2.75 MJ output) was applied. This grey electricity mix is composed of the following energy sources: natural gas (81.25%), coal (10.93%), nuclear energy (4.42%), oil products (1.51%), and other non-renewable fuels (approximately 1.89%). The Global Warming Potential associated with this electricity mix is 6.23×10^{-1} kg CO₂-equivalent per kWh.

Description of scenarios for modules beyond A1–A3:

A4 – Transport to construction site:

A fixed distance of 300 km from Lørenskog to end-user is assumed, modeled using EURO 6 diesel truck transport.

A5 - Installation

Installation is done by hand and therefore the impact is neglectable. A 15% installation loss is applied.

C1 – Deconstruction:

Firesafe FSP is a finishing material that adheres to other materials. The impact generated during the demolition phase is negligible and falls within the cutoff criteria.

C2 – Transport to EoL processing:

100% of the product is transported for recycling over a distance of 50 km, modeled with truck transport.

C3 – Waste processing:

As a finishing material that bonds to other substrates, Firesafe FSP generates negligible impact during the waste processing phase, falling within the cutoff criteria.

C4 – Disposal:

In stage C4, 100% of Firesafe FSP is disposed of via landfill.

D – Module D (recovery):

Module D shows no environmental benefits, as landfilling in C4 prevents any recovery or reuse.

DECLARATION OF SVHC

The product does not contain SVHC

REFERENCES

CE Delft. (2010). Handboek Schaduwprijzen. Opgehaald van <https://ce.nl/publicaties/handboek-schaduwprijzen-waardering-en-weging-van-emissies-en-milieueffecten/>

ISO. (2006). 'ISO 14025: Environmental labels and declarations -- Type III environmental declarations -- Principles and procedures', International Organization for Standardization, ISO14025:2006.

ISO. (2006). 'ISO 14040: Environmental management - Life cycle assessment – Principles and Framework', International Organization for Standardization, ISO14040:2006.

ISO. (2006). 'ISO 14044: Environmental management - Life cycle assessment - Requirements and guidelines', International Organization for Standardization, ISO14044:2006.

NEN. (2013). 'NEN-EN 15804: Duurzaamheid van bouwwerken - Milieuverklaringen van producten - Basisregels voor de productgroep bouwproducten', NEN-EN 15804:2012+A1:2013.

NMD. (2025). Bepalingsmethode 'Milieuprestatie Bouwwerken' versie 1.2 inclusief de bijbehorende wijzigingsbladen.

NMD. (2022, March). Environmental Performance Assessment Method for Construction Works. Opgehaald van https://milieudatabase.nl/wp-content/uploads/2022/05/Bepalingsmethode_Milieuprestatie_Bouwwerken_maart_2022_Engels.pdf

TNO. (sd). Toxiciteit heeft z'n prijs : schaduwprijzen voor (eco-)toxiciteit en uitputting van abiotische grondstoffen binnen DuboCalc. Opgehaald van https://puc.overheid.nl/rijkswaterstaat/doc/PUC_119145_31/